

2) FINISH: N/A

3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1

7) WEIGHT: 6.3 lbs

8

8) PRESS FIT D5346-3 INTO D5349-1. IT IS ACCEPTABLE USE MAGNABOND ADHESIVE, REMOVE EXCESS ADHESIVE FROM BUSHING HOLE
9) TORQUE MS21042L3 NUTS TO 20-25 in-lb (2.3-2.8 N-m)

TORQUE MS21042L5 NUTS TO 100-140 in-lb (11.3-15.8 N-m) 10) ASSEMBLE D2690-11 WITH AN416-1 AS SHOWN



Α	A NEW ISSUE RF			RF	15.08.10
REV.	/. E		DESCRIPTION	BY	DATE
DESIGN		RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWN		RF			
CHECKED		AK	DRAWING NO.		REV. A
MFG. APPR.		JFS	D5349		SHEET 1 OF 6
APPROVED		HS	TITLE		SCALE
DE APPR.		D\$=	R44 BEAM ASSEMBLY	•	NTS
DATE	DATE 15.08.10		COPYRIGHT © 2015 BY DART AEROSPACE LTD  THIS DOCUMENT IS PRIVATE ANY PUP CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS  NOT TO BE USED FOR ANY PUPPOSE OR COMPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT		

3









